Uncontrolled document as of April 9, 2014. Refer to website for up to date specifications.











## M6 2330 LED Flashlight

Talk about durable. The M6 2330 LED Flashlight uses a 1 watt Luxeon LED for intense brightness, extended battery burn time, and long lamp life. The strong body is CNC-machined aluminum with knurled grip for a secure handle. Plus, the convenient push button tail cap switch has a safety lockout feature to prevent inadvertent battery depletion or accidental activation. The M6 comes with a free Cordura® holster with back-up battery pouch. Powered by 2 CR123 lithium cells (included).

Body Material: Aluminum

Minimum Pack 6 ea.

Packaged Weight: 9.5 oz.



**M6 2330 LED Flashlight Specifications** 

**M6 2330 LED Flashlight Configurations** 

Cat. # Description

	High			
LIGHT SOURCE	LED			
BATTERIES	2 CR123 Lithium (Included)			
CHARGE TIME	N/A			
VOLTAGE	6			
LENGTH	5.51" (14 cm)			
WEIGHT W BATTERIES	5.5 oz. (0.16 kg)			
WEIGHT WO BATTERIES	4.4 oz. (0.12 kg)			

,			
1	FL1 STANDARD	High	
LIGHT OUTPUT	345	100 LUMENS	
RUNTIME (hoursimin)	0	6h	
BEAM DISTANCE (meters)	I	93m	
PEAK BEAM INTENSITY (candela)		2184cd	
WATER RESISTANT		IPX4	IPX4

2330 M	M6 2330 LED Flashlight (Carded)

## **NSN List**

NSN #	Description
6230-01-523-4709	2330C Black

## M6 2330 LED Flashlight Accessories

Cat. #	Description
610	Front Sight Mount
620	Side Sling Mount
630	Foregrip Mount
770	Universal Helmet Light Holder
2326	Remote Pressure Switch
2327	Cordura® Holster
2322OR	Traffic Wand (Orange)
2322YW	Traffic Wand (Yellow)
2325BLUE	M6 Blue Filter Cap
2325RED	M6 Red Filter Cap

Pelican Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com