

LIGHTS
2410
StealthLite LED



Submersible 

StealthLite™ 2410 LED Flashlight

Same features as the [StealthLite 2400 Flashlight](#) but with the LED module that produces a true, bright collimated LED beam. The 2410 is corrosion proof, resistant to extreme temperatures, and submersible. It is powered by 4 AA alkaline cells (included). For hands-free operation, attach it to your hard hat with our optional helmet light holder.

Body Material: EXL Resin

Minimum Pack 6 ea.

Packaged Weight: 8.4 oz.



Black








Yellow

StealthLite™ 2410 LED Flashlight Specifications

StealthLite™ 2410 LED Flashlight Configurations

Cat. #	Description
2410	StealthLite™ 2410 LED Flashlight (Coated)

High	
LIGHT SOURCE	LED
BATTERIES	4 AA Alkaline (Included)
CHARGE TIME	N/A
VOLTAGE	6
LENGTH	7" (17.8 cm)
WEIGHT w/ BATTERIES	7.3 oz. (0.21 kg)
WEIGHT w/o BATTERIES	3.7 oz. (0.1 kg)

FL 1 STANDARD	High	
LIGHT OUTPUT 	126 LUMENS	
RUNTIME (hours/min) 	7h 30m	
BEAM DISTANCE (meters) 	161m	
PEAK BEAM INTENSITY (candela) 	6500cd	
WATERPROOF & SUBMERSIBLE 	IPX7	IPX7

2410 StealthLite™ 2410 LED Flashlight (Cardea)

2410PL StealthLite™ 2410 LED Flashlight (35mm) w/ Photoluminescent Shroud

StealthLite™ 2410 LED Flashlight Accessories

Cat. #	Description
700	Helmet Light Holder
750	Helmet Light Holder
770	Universal Helmet Light Holder
2407	Cordura® Holster
2413PL	Photoluminescent Shroud

StealthLite™ 2410 LED Flashlight Approvals

IECEx

ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T135??C Da IP66



Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com