



## M11 Rechargeable 8050 Flashlight

The M11 Flashlight uses a rechargeable 4 C Ni-MH battery stick and a hi-pressure Xenon lamp to generate powerful, bright pre-focused beam. The body is molded with an all weather no-slip grip pattern. The new castle top shroud alerts user when light is left on while standing head down. The push button on/off switch operates easily even when wearing thick gloves.

Options include fast chargers, direct wiring, 12V adapters, 110V transformers and more. The fast charger fully charges the Ni-MH battery stick in 4 to 5 hours, preparing the M11 for a full day's work. The fast charger can be mounted horizontally or upright and an LED indicator illuminates when the M11 is charged. Mount the M11 in vehicles using the 12V adapter or direct wiring kit. The durable rechargeable Ni-MH battery pack can take a charge over 1,000 times.

**CAUTION:** This Pelican Flashlight is a high output Professional Grade Lighting Product and can generate significant heat and light intensity. Do not leave activated flashlight unattended. Do not cover activated flashlight. Do not place activated flashlight against combustible material or material that could be damaged by heat. Keep activated flashlight well ventilated. If the lamp is activated while in a case or other container, the lamp could overheat and cause damage to surrounding materials.

Body Material: Xenoy Polymer Resin

**Minimum Pack 1 ea.**

**Packaged Weight: 3.3 lbs.**



Black








Yellow

## M11 Rechargeable 8050 Flashlight Specifications

## M11 Rechargeable 8050 Flashlight Configurations

Cat. #	Description
8050	M11 Rechargeable 8050 Flashlight (Recessed)

High	
<b>LIGHT SOURCE</b>	Xenon
<b>BATTERIES</b>	4 C Ni-MH (Included)
<b>CHARGE TIME</b>	4-5 hours
<b>VOLTAGE</b>	4.8
<b>LENGTH</b>	11.25" (28.6 cm)
<b>WEIGHT w/ BATTERIES</b>	17.92 oz. (0.51 kg)
<b>WEIGHT w/o BATTERIES</b>	7 oz. (0.2 kg)

FL1 STANDARD	High	
<b>LIGHT OUTPUT</b> 	154 LUMENS	
<b>RUNTIME (hours:min)</b> 	2h 15m	
<b>BEAM DISTANCE (meters)</b> 	257m	
<b>PEAK BEAM INTENSITY (candela)</b> 	16535cd	
<b>WATER RESISTANT</b> 	IPX4	IPX4

8050	M11 Rechargeable 8050 Flashlight (Boxed)
8050AC110F	M11 8050 System w/110V Transformer (Fast Charger)
8051B	M11 8050 Flashlight w/Battery Only (Boxed)

### NSN List

NSN #	Description
6230-01-477-3516	8050AC110T Black

### M11 Rechargeable 8050 Flashlight Accessories

Cat. #	Description
<b>8054</b>	<b>Replacement Lamp Module</b>
<b>8057</b>	<b>Cordura® Holster</b>
<b>8069</b>	<b>Replacement NiMH Battery Pack</b>
<b>6057F</b>	<b>110V Transformer for Fast Charger</b>
<b>6061F</b>	<b>Direct Wiring Rig for Fast Charger</b>
<b>8060FBC</b>	<b>Bank Charger Fast</b>
<b>8052OR</b>	<b>Traffic Wand (Orange)</b>
<b>8052YW</b>	<b>Traffic Wand (Yellow)</b>
<b>8056F</b>	<b>12V Plug-in for Fast Charger</b>
<b>8070</b>	<b>Desk/Dash Fast Charger Base Unit</b>

#### Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
 e-mail: [CSR.Consumer@pelican.com](mailto:CSR.Consumer@pelican.com) • [www.pelican.com](http://www.pelican.com)