Uncontrolled document as of April 7, 2014. Refer to website for up to date specifications.







### **KingLite™ 4000 Flashlight**

The KingLite is a heavy duty, high powered spotlight packed with features. It uses a unique dual filament Xenon lamp that produces a bright beam that cuts through thick smoke, fog, and dust. The body is made of unbreakable ABS resin with a polycarbonate lens and thermoplastic rubber shroud that resists chemicals and corrosion. Two reflectors are included: a modified spot (stippled for a wide beam) and a laser spot (smooth for a tight collimated beam).

The dual direction switch is easy to operate, even with thick gloves. And there's a locking slide feature to prevent accidental activation. The pistol grip/lantern handle quickly converts to multiple positions for flexibility. The 4000 also comes with a shock absorbing internal battery module that protects both the cells and the lamp from hard knocks. Powered by 8 D alkaline cells.

Body Material: ABS Resin

Minimum Pack 1 ea. Packaged Weight: 2.2 lbs.







**KingLite™ 4000 Flashlight Specifications** 

**KingLite™ 4000 Flashlight Configurations** 

Cat. # Description

High				
LIGHT SOURCE	Xenon			
BATTERIES	8 D Alkaline (Not included)			
CHARGETIME	N/A			
VOLTAGE	12			
LENGTH	9.37" (23.8 cm)			
WEIGHT W BATTERIES	74.08 oz. (2.1 kg)			
WEIGHT wio BATTERIES	30.4 oz. (0.86 kg)			

		(	
	WEIGHT W BATTERIES	74.08 oz. (2.1 kg)	
	WEIGHT w/o BATTERIES	30.4 oz. (0.86 kg)	
	FL1 STANDARD	High	
LIGHT OUTPUT	345	249 LUMENS	
RUNTIME tours/min)	0	11h	
BEAM DISTANCE (meters)		106m	
EAK BEAM NTENSITY (candela)		3168cd	

IPX7

4000	KingLite™ 4000 Flashlight (Boxed)

#### **NSN** List

6230-01-492-5816 4000 Black	NSN #	Description
0250 01 152 5010 1000 Black	6230-01-492-5816	4000 Black

## **KingLite™ 4000 Flashlight Accessories**

Cat. #	Description
4003	KingLite™ 4000 Xenon Dual Filament Lamp
4006	Wall Mount Bracket

# KingLite<sup>™</sup> 4000 Flashlight Approvals



N.I. Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G. AMBIENT TEMP 0????C TO 40????C

IPX7



N.I. Class I, Div. 2; Gp. CD, T1.

#### Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 e-mail:CSR.Consumer@pelican.com • www.pelican.com