Uncontrolled document as of April 7, 2014. Refer to website for up to date specifications.









Little Ed[™] 3610 LED Photoluminescent Flashlight

Same as the 3610 Flashlight but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight. The Little Ed 3610PL is powered by 4 AA alkaline cells (included). Body Material: EXL Resin

Minimum Pack 1 ea. Packaged Weight: 11.1 oz.



Little Ed[™] 3610 LED Photoluminescent Flashlight Specifications Little Ed[™] 3610 LED Photoluminescent Flashlight Configurations Cat. # Description



| | High | | |
|--|-------------------------|--------------------------|--|
| | LIGHT Source | LED | |
| | BATTERIES | 4 AA Alkaline (Included) | |
| | CHARGE TIME | N/A | |
| | VOLTAGE | 6 | |
| | LENGTH | 7.51"(19.1 cm) | |
| | WEIGHT W BATTERIES | 10.5 oz. (0.3 kg) | |
| | WEIGHT w/o BATTERIES | 6.9 oz. (0.2 kg) | |
| 1 | FL1 STANDARD | High | |
| | | | |
| LIGHT OUTPUT | 342 | 126 LUMENS | |
| LIGHT OUTPUT RUNTIME (hours/min) | 34×2 | | |
| OUTPUT | <i>¥</i> , 0 V | LUMENS | |
| OUTPUT RUNTIME (hoursimin) BEAM DISTANCE | ;;'⊖ \ | LUMENS 7h 30m | |

Little Ed[™] 3610 LED Photoluminescent Flashlight Approvals

ECEX

c@us

Intertek 3091325

ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T135??C Da IP66

Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 e-mail:CSR.Consumer@pelican.com • www.pelican.com

