



Save as PDF



Peli lights - Zone 1 Peli Light - Zone 1 Incandescent Worklights



The Peli MityLite 1900Z1 is a powerful, compact torch that's ATEX certified safe for use in hazardous Zone 1 (Category 2) locations. This torch is perfect for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue. It's powered by 2 AAA alkaline cells and submersible.



Peli lights - Zone 1 Peli Light - Zone 1 Incandescent Worklights ANSI FL1 Specifications

LIGHT SOURCE.	High Xenon	
BATTERIES	2 AAA Alkaline (Included)	
CHARGE TIME	N/A	
VOLTAGE	3	
LENGTH	10.4 cm (4.09")	
WEIGHT W/ BATTERIES	0.09 kg (3 oz.)	
WEIGHT W/O BATTERIES	0.02 kg (0.75 oz.)	

LIGHT OUTPUT	FL1 STANDARD	High	
RUNTIME (hours/min)		1h 30m	
BEAM DISTANCE (meters)		45m	
PEAK BEAM INTENSITY (candela)		571cd	
WATER RESISTANT			

Materials

Body	Lens	Shroud	Switch Type
EXL	Polycarbonate	Xenoy	Twist On/Off Lens Shroud
Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
N/A	Phosphore/Bronze	Ethylene Propylene	N/A

Configuration

Cat. #	Description
Peli lights - Zone 1 Peli Light - Zone 1 Incandescent Worklights Accessories	
Cat. #	Description
1904Z1	MityLite 1900 Zone 1 Lamp Module

Approvals

CE Ex - II 2G Ex e ib IIB T4, II 2D Ex ibD 21 IP67 T100?
??C
Certificate: ITS09ATEX26184X