

LIGHTS
9410L
LED

NEW



9410L LED Lantern

LESS THAN 3 LBS + 1131 LUMENS =
BRIGHTEST & LIGHTEST IN ITS CLASS

At less than 3 pounds and 1131 lumens, the new 9410L LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Lithium-Ion batteries illuminate a distance of 475 yards (435 meters). And it's loaded with innovative technology and features you have come to expect from Pelican:

- 120° rotating head
- Run time: 9 hrs. (low)/3.75 hrs. (high)
- Battery status indicator
- 3 mode switch (High, Low, Flashing)
- 8.75" x 3.75" x 4.0" (22.2 x 9.5 10.2 cm) L x W x H
- Shoulder strap included

Whether you're on a USAR team or the 3rd shift at a refinery, you'll appreciate the compact size and high output of the new 9410L LED Lantern.

Approved to NFPA (National Fire Protection Association) 1901

Body Material: ABS

Minimum Pack 1 ea.



Black



Yellow

9410L LED Lantern Specifications






9410L LED Lantern Configurations

	High	Low
LIGHT SOURCE	LED	LED (Low)
BATTERIES	0 7.4V, 6.6Ahr. Lithium-Ion (Included)	
CHARGE TIME	7-8 hours	
VOLTAGE	7.4	
LENGTH	8.75" (22.2 cm)	
WEIGHT w/ BATTERIES	44.7 oz. (1.27 kg)	
WEIGHT w/o BATTERIES	0 oz. (0 kg)	

Cat. #	Description
9410L	9410L LED Lantern (Boxed)

9410L LED Lantern Accessories

Cat. #	Description
6057F	110V Transformer for Fast Charger
9419L	9410L Replacement Battery
9416L	Desk/Dash Fast Charger Base Unit
6061F	Direct Wiring Rig for Fast Charger
8056F	12V Plug-in for Fast Charger
9413DL	Diffuser Lens for 9410/9415

	FL 1 STANDARD	High	Low		Flashing
LIGHT OUTPUT		1131 LUMENS	558 LUMENS		1131 LUMENS
RUNTIME (hours/min)		3h 45m	9h		7h 30m
BEAM DISTANCE (meters)		435m	294m		435m
PEAK BEAM INTENSITY (candela)		47280cd	21576cd		47280cd
WATER RESISTANT		IPX4	IPX4	IPX4	IPX4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com