

LIGHTS
2400NVG
StealthLite NVG



Submersible 

StealthLite™ 2400NVG Flashlight

This flashlight has the same features of the [StealthLite™ 2400 Flashlight](#) but equipped with a special lens that alters the color spectrum and cut the candlepower to preserve night vision.

Body Material: LEXAN EXL Resin

Minimum Pack 6 ea.



Black

StealthLite™ 2400NVG Flashlight Specifications






StealthLite™ 2400NVG Flashlight Configurations

Cat. #	Description
2400NVG	STEALTHLITE™ 2400NVG Flashlight (Corded)

High	
LIGHT SOURCE	Xenon
BATTERIES	4 AA Alkaline (Included)
CHARGE TIME	N/A
VOLTAGE	6
LENGTH	6.49" (16.5 cm)
WEIGHT w/ BATTERIES	7.1 oz. (0.2 kg)
WEIGHT w/o BATTERIES	3.5 oz. (0.1 kg)

StealthLite™ 2400NVG Flashlight Accessories

Cat. #	Description
700	Helmet Light Holder
750	Helmet Light Holder
770	Universal Helmet Light Holder
2404	StealthLite™ 2400 Xenon Lamp Module
2407	Cordura® Holster

FL 1 STANDARD		High	
LIGHT OUTPUT			
RUNTIME (hours/min)			
BEAM DISTANCE (meters)			
PEAK BEAM INTENSITY (candela)			
WATERPROOF & SUBMERSIBLE		IPX7	IPX7

StealthLite™ 2400NVG Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.



Class I, Div. 2; Gp. ABCD, T3A.



Intertek
3091325

Class I, Div. 1, GP.D, CL.I, Zone 1, GP. IIA OPERATING TEMP. CLASS T3 CONFORMS TO STD. UL 783 Energizer E91 only

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com