Uncontrolled document as of April 7, 2014. Refer to website for up to date specifications.











PM6 3330 LED Flashlight

Same as the 3320 Flashlight but in an LED version. The PM6 3330 LED Flashlight is made of light weight Xenoy polymer that's corrosion proof, resistant to extreme temperatures, and extremely strong. It uses a 1 watt LED and is powered by 2 CR123 lithium cells (included). A black oxide coated steel clip is built in and the one-handed tail switch activates the 3330 on, for constant light or momentary blink.

Body Material: Xenoy Polymer Resin

Minimum Pack 6 ea. Packaged Weight: 5.9 oz.







PM6 3330 LED Flashlight Specifications

PM6 3330 LED Flashlight Configurations

Cat. # Description

High					
LIGHT SOURCE	LED				
BATTERIES	2 CR123 Lithium (Included)				
CHARGETIME	N/A				
VOLTAGE	6				
LENGTH	5.27" (13.4 cm)				
WEIGHT W BATTERIES	3.45 oz. (0.1 kg)				
WEIGHT WO BATTERIES	2.23 oz. (0.06 kg)				

ì	FL1 STANDARD	High	
LIGHT OUTPUT	える	90 LUMENS	
RUNTIME (hours/min)	0	4h 45m	
BEAM DISTANCE (meters)		88m	
PEAK BEAM INTENSITY (candela)		1959cd	
WATER RESISTANT		IPX4	IPX4

3330	PM6 3330 LED Flashlight (Carded)

PM6 3330 LED Flashlight Accessories

Cat. #	Description
770	Universal Helmet Light Holder

Pelican Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com