



L1™ 1930 LED Flashlight

With a long lamp life and extended battery burn time, you won't be left in the dark with the L1 flashlight. The polycarbonate body is resistant to chemicals, water and corrosion. The convenient tail switch for constant on/momentary is easy to operate. The L1 is perfect for close quarter use. Packaged with 4 LR 44 1.5V alkaline coin cells, a break-a-way safety lanyard, and colored lens discs to preserve night vision. This handy flashlight offers a lot for its size.

Body Material: Polycarbonate Resin

Minimum Pack 12 ea.

Packaged Weight: 0.8 oz.



Black








Yellow

L1™ 1930 LED Flashlight Specifications

L1™ 1930 LED Flashlight Configurations

Cat. #	Description
--------	-------------

High	
LIGHT SOURCE	LED
BATTERIES	4 LR 44 Alkaline (Included)
CHARGE TIME	N/A
VOLTAGE	6
LENGTH	2.64" (6.7 cm)
WEIGHT w/ BATTERIES	0.9 oz. (0.03 kg)
WEIGHT w/o BATTERIES	0.63 oz. (0.02 kg)

FL1 STANDARD	High	
LIGHT OUTPUT 	12 LUMENS	
RUNTIME (hours:min) 	4h 15m	
BEAM DISTANCE (meters) 	17m	
PEAK BEAM INTENSITY (candela) 	70cd	
WATER RESISTANT 	IPX4	IPX4

L1™ 1930 LED Flashlight Approvals



Listed 4S67/E184884 Class I, Div. 1 Gps.A,B,C,D, .



Ex ia IIC T4 IP65 IEC Ex TSA 06.0021X

1930	L1™ 1930 LED Flashlight (Carded)
1930M	L1™ 1930 LED Flashlight Merchandiser Display

NSN List

NSN #	Description
6230-01-502-6253	1930CR
6230-01-496-3638	1930 Zone 0 (Peli)
6230-01-496-3101	1930 Visible Green Finger Light
6230-01-502-6254	1930CB
6230-01-491-0793	1930IR Boxed
6230-01-502-6248	1930C

L1™ 1930 LED Flashlight Accessories

Cat. #	Description
1939	Four 1.5V Alkaline Coin Cell Batteries
1946B	L1 1930 LED Attachment Kit

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com