



Submersible

StealthLite™ 2410 LED Photoluminescent Flashlight

Same features as the [StealthLite 2410 LED Flashlight](#) but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight. It is powered by 4 AA alkaline cells (included), submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures.

Body Material: EXL Resin

Minimum Pack 6 ea.

Packaged Weight: 8.4 oz.



Yellow

StealthLite™ 2410 LED Photoluminescent Flashlight Specifications

StealthLite™ 2410 LED Photoluminescent Flashlight Configurations

Cat. #	Description
--------	-------------

High		
LIGHT SOURCE	LED	
BATTERIES	4 AA Alkaline (Included)	
CHARGE TIME	N/A	
VOLTAGE	6	
LENGTH	7" (17.8 cm)	
WEIGHT w/ BATTERIES	7.3 oz. (0.21 kg)	
WEIGHT w/o BATTERIES	3.7 oz. (0.1 kg)	

FL1 STANDARD	High	
LIGHT OUTPUT		126 LUMENS
RUNTIME (hours/min)		7h 30m
BEAM DISTANCE (meters)		161m
PEAK BEAM INTENSITY (candela)		6500cd
WATERPROOF & SUBMERSIBLE		IPX7
		IPX7

2410PL StealthLite™ 2410 LED Photoluminescent Flashlight (Carded)

StealthLite™ 2410 LED Photoluminescent Flashlight Accessories

Cat. #	Description
700	Helmet Light Holder
750	Helmet Light Holder
770	Universal Helmet Light Holder
2407	Cordura® Holster

StealthLite™ 2410 LED Photoluminescent Flashlight Approvals

IECEx

ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T135??C Da IP66



Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com