

**LIGHTS**  
**3610**  
Little Ed LED



**Little Ed™ 3610 LED Flashlight**

The 3610 is a right angle flashlight that uses our latest “Deep Mount” LED technology, delivering impressive lumens and lux performance. The stainless steel mounting clip allows for hands free applications. The body is made of tough ABS resin that's corrosion proof and resistant to extreme temperatures. It is powered by 4 AA alkaline cells (included).

Body Material: EXL Resin

**Minimum Pack 1 ea.**

**Packaged Weight: 11.1 oz.**



Black



Yellow

**Little Ed™ 3610 LED Flashlight Specifications Little Ed™ 3610 LED Flashlight Configurations**






**Cat. # Description**

High	
<b>LIGHT SOURCE</b>	LED
<b>BATTERIES</b>	4 AA Alkaline (Included)
<b>CHARGE TIME</b>	N/A
<b>VOLTAGE</b>	6
<b>LENGTH</b>	7.51" (19.1 cm)
<b>WEIGHT w/ BATTERIES</b>	10.5 oz. (0.3 kg)
<b>WEIGHT w/o BATTERIES</b>	6.9 oz. (0.2 kg)

3610	Little Ed™ 3610 LED Flashlight (Carded)
3610PL	Little Ed™ 3610 LED Flashlight w/ Photoluminescent Shroud

### Little Ed™ 3610 LED Flashlight Accessories

Cat. #	Description
2413PL	Photoluminescent Shroud

FL 1 STANDARD		High	
<b>LIGHT OUTPUT</b>		126 LUMENS	
<b>RUNTIME (hours/min)</b>		7h 30m	
<b>BEAM DISTANCE (meters)</b>		161m	
<b>PEAK BEAM INTENSITY (candela)</b>		6500cd	
<b>WATERPROOF &amp; SUBMERSIBLE</b>		IPX7	IPX7

### Little Ed™ 3610 LED Flashlight Approvals

**IECEx** ITS.09.0017X Ex ia IIC T4 Ga, Ex ia IIIC T135??C Da IP66

**ETL US** Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4  
Intertek 3091325

#### Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [CSR.Consumer@pelican.com](mailto:CSR.Consumer@pelican.com) • [www.pelican.com](http://www.pelican.com)