Uncontrolled document as of April 9, 2014. Refer to website for up to date specifications.









MityLite™ 1960 LED Flashlight

An evolution of our popular MityLite™ 1900, the 1960 LED brings the latest in LED technology. Built compact and lightweight to fit inside your pocket yet bright enough to illuminate with 24 lumens. It comes with a twist-on shroud. It's ABS resin body resists chemicals, corrosion, and extreme temperatures.

Body Material: Xenoy

Minimum Pack 12 ea.





MityLite™ 1960 LED Flashlight Specifications MityLite™ 1960 LED Flashlight Configurations

Cat. # Description

III-ab				
LIGHT SOURCE	High LED			
BATTERIES	2 AAA Alkaline (Included)			
CHARGE TIME				
VOLTAGE	3			
LENGTH	5.48" (13.9 cm)			
WEIGHT W BATTERIES	1.9 oz. (0.05 kg)			
WEIGHT w/o BATTERIES	1.1 oz. (0.03 kg)			
FL1 STANDARD	High			
ايلا				

1	FL1 STANDARD	High	
LIGHT OUTPUT	シイ	24 LUMENS	
RUNTIME (hours/min)	0	3h	
BEAM DISTANCE (meters)		51m	
PEAK BEAM INTENSITY (candela)		657cd	
MATERPROOF & UBMERSIBLE		IPX7	IPX7

1960

MityLite[™] 1960 LED Flashlight (Carded)

Pelican Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com