



MityLite™ 2340NVG Flashlight

This compact flashlight has the same features of the [MityLite™ 2340 Flashlight](#) but equipped with a special lens that alters the color spectrum and cut the candlepower to preserve night vision.

Body Material: Xenoy Polymer Resin

Minimum Pack 6 ea.



Black

MityLite™ 2340NVG Flashlight Specifications [MityLite™ 2340NVG Flashlight Configurations](#)






Cat. #	Description
--------	-------------

High	
LIGHT SOURCE	Xenon
BATTERIES	2 AA Alkaline (Included in select packaging)
CHARGE TIME	N/A
VOLTAGE	3
LENGTH	6.25" (15.9 cm)
WEIGHT w/ BATTERIES	3.5 oz. (0.1 kg)
WEIGHT w/o BATTERIES	1.86 oz. (0.05 kg)

2340NVG MityLite™ 2340NVG Flashlight (Boxed)

MityLite™ 2340NVG Flashlight Accessories

Cat. #	Description
750	Helmet Light Holder
770	Universal Helmet Light Holder
2304	MityLite™ 2340NVG Lamp Module
2357	Cordura® Holster

FL 1 STANDARD		High	
LIGHT OUTPUT			
RUNTIME (hours/min)			
BEAM DISTANCE (meters)			
PEAK BEAM INTENSITY (candela)			
WATER RESISTANT		IPX4	IPX4

MityLite™ 2340NVG Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.



Class I, Div. 2; Gp. ABCD, T3A.



Ex ib e IIC T4 IP67 IEC Ex TSA 06.0021X



Class I, Div. 1; Gps.C,D T3, Conforms to STD UL783

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
 e-mail: CSR.Consumer@pelican.com • www.pelican.com