

**LIGHTS**  
**2690**  
HeadsUp Lite



**HeadsUp Lite™ 2690 LED Headlight**

Regardless of the season, Pelican's new 2690 HeadsUp Lite™ won't leave you in the dark. With 60 lumens of LED light, 10 hours of battery burn time and weighing in at 4.1 ounces, it's brighter, more efficient, compact and lighter than other headlamps in its class. The no-nonsense rotary bezel switch is easy to operate, even when wearing bulky gloves.

The 2690 is made of impact and chemical resistant ABS and it's water resistant for all-weather use. It comes with an adjustable and comfortable cloth strap, as well as a heavy duty rubber strap that will not slip off your climbing helmet. Pelican's new 2690 HeadsUp Lite™ is engineered for those who take the outdoors seriously.

Use your head. Get the 2690 HeadsUp Lite™ from Pelican.

The Pelican 2690 is now ATEX & IECEx underground mining approved.

2690 HeadsUP Lite manufactured prior to April, 2012 were improperly marked with IECEx EXTr test report number rather than the IECEx Certificate number. Other than the use of the ExTR number rather than the required Certificate number in the equipment markings, the equipment is in full compliance with both the ExTR and Certificate.

Body Material: ABS

**Minimum Pack 1 ea.**



Black






**HeadsUp Lite™ 2690 LED Headlight Specifications**

**HeadsUp Lite™ 2690 LED Headlight Configurations**

**Cat. # Description**

2690 HeadsUp Lite™ 2690 LED Headlight (Carded)

High	
<b>LIGHT SOURCE</b>	LED
<b>BATTERIES</b>	3 AAA Alkaline (Included)
<b>CHARGE TIME</b>	
<b>VOLTAGE</b>	4.5
<b>LENGTH</b>	2.81" (7.1 cm)
<b>WEIGHT w/ BATTERIES</b>	4.1 oz. (0.12 kg)
<b>WEIGHT w/o BATTERIES</b>	2.8 oz. (0.08 kg)

FL 1 STANDARD		High	
<b>LIGHT OUTPUT</b>		60 LUMENS	
<b>RUNTIME (hours/min)</b>		10h 30m	
<b>BEAM DISTANCE (meters)</b>		81m	
<b>PEAK BEAM INTENSITY (candela)</b>		1664cd	
<b>WATERPROOF &amp; SUBMERSIBLE</b>		IPX7	IPX7

### HeadsUp Lite™ 2690 LED Headlight Approvals



I M1 Ex ia I Ma, II 1 G Ex ia IIC T4 Ga, Ex ia IIIC T65??C Da IP65  
**Certificate:** TRL 08ATEX11184X



IECEx TRC 11.0010X Ex ia I Ma, Ex ia IIC T4 Ga, Ex ia IIIC T65??



Class I II III Div. 1 GRPS ABCDEFG T4



Class I II III Div. 1 GRPS ABCDEFG T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [CSR.Consumer@pelican.com](mailto:CSR.Consumer@pelican.com) • [www.pelican.com](http://www.pelican.com)