



Submersible

SabreLite™ 2010 LED Photoluminescent Flashlight

Same features as the [SabreLite 2010 LED Flashlight](#) but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight.

Body Material: EXL

Minimum Pack 1 ea.

Packaged Weight: 13.4 oz.








Yellow

SabreLite™ 2010 LED Photoluminescent Flashlight Specifications

SabreLite™ 2010 LED Photoluminescent Flashlight Configurations

Cat. #	Description
--------	-------------

High		
LIGHT SOURCE	LED	
BATTERIES	3 C Alkaline (Not included)	
CHARGE TIME	N/A	
VOLTAGE	4.5	
LENGTH	8.11" (20.6 cm)	
WEIGHT w/ BATTERIES	13.4 oz. (0.38 kg)	
WEIGHT w/o BATTERIES	5.36 oz. (0.15 kg)	

FL 1 STANDARD High			
LIGHT OUTPUT		109 LUMENS	
RUNTIME (hours/min)		32h	
BEAM DISTANCE (meters)		144m	
PEAK BEAM INTENSITY (candela)		5189cd	
WATERPROOF & SUBMERSIBLE		IPX7	IPX7

2010PL SabreLite™ 2010 LED Photoluminescent Flashlight (Carded)

SabreLite™ 2010 LED Photoluminescent Flashlight Accessories

Cat. #	Description
8052OR	Traffic Wand (Orange)
8052YW	Traffic Wand (Yellow)

SabreLite™ 2010 LED Photoluminescent Flashlight Approvals

IECEx

ITS11.0023 Ex ia IIC T4 Ga (Energizer), 145??C (Duracell), T3 (P



Class I II III Division 1 Groups ABCDFG T4 (Energizer), 145??C (Duracell), T3 (Panasonic)

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com