

LIGHTS
3715
LED



3715 LED Flashlight

Pelican leads the way yet again with its new right angle light. Featuring downcast LEDs for illuminating your path, the new 3715 LED light also features 174 lumens (high) and 95 lumens (low), and a signaling mode.

Another first is a built in battery life indicator so you will know your light's battery level before you go in.

Compact, rugged, and lightweight, the 3715 LED light contains the latest technology, Pelican's legendary build quality and [lifetime guarantee of excellence](#).

The new 3715 LED - Now you can WATCH YOUR STEP.

Body Material: ABS

Minimum Pack 1 ea.



Black



Yellow

3715 LED Flashlight Specifications






3715 LED Flashlight Configurations

	High	Low
LIGHT SOURCE	LED	LED (Low)
BATTERIES	4 AA Alkaline (Not included)	
CHARGE TIME		
VOLTAGE	6	
LENGTH	5.36" (13.6 cm)	
WEIGHT w/ BATTERIES	14.4 oz. (0.41 kg)	
WEIGHT w/o BATTERIES	11 oz. (0.31 kg)	

Cat. #	Description
3715	3715 LED Flashlight (Boxed)

3715 LED Flashlight Accessories

Cat. #	Description
3713PL	3715/3765 Photoluminescent Shroud

FL 1 STANDARD	High	Low	Downcast	Flashing
LIGHT OUTPUT 	174 LUMENS	95 LUMENS	32 LUMENS	142 LUMENS
RUNTIME (hours/min) 	4h 45m	8h 30m	31h	10h
BEAM DISTANCE (meters) 	278m	175m	28m	278m
PEAK BEAM INTENSITY (candela) 	19389cd	8051cd	197cd	19389cd
WATER RESISTANT 	IPX4	IPX4	IPX4	IPX4

3715 LED Flashlight Approvals



IECEx TRC 12.0006X Ex ia IIC T4 Ga



Class I, Div. 1 Groups ABCD Operating Temp. Class T4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com