




Save as PDF



Peli lights - Zone 1 Peli Lights - Alkaline Incandescent Worklights

Same features as the SabreLite™ 2000 with static-dissipation materials body. SabreLite™ 2000Z1 is ATEX certified safe for use in hazardous Zone 1 (Category 2) locations, and is perfect for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



Materials

Peli lights - Zone 1 Peli Lights - Alkaline Incandescent Worklights ANSI FL1 Specifications

High	
LIGHT SOURCE	Xenon
BATTERIES	3 C Alkaline (Not included)
CHARGE TIME	N/A
VOLTAGE	4.5
LENGTH	19.8 cm (7.79")
WEIGHT W/ BATTERIES	0.13 kg (4.5 oz.)
WEIGHT W/O BATTERIES	0.15 kg (5.31 oz.)

Body	Lens	Shroud	Switch Type
EXL	Polycarbonate	Xenoy	Twist On/Off Lens Shroud
Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
ABS	Stainless Steel	Ethylene Propylene	N/A

Configuration

Cat. #	Description
--------	-------------

Peli lights - Zone 1 Peli Lights - Alkaline Incandescent Worklights Accessories

Cat. #	Description
2004Z1	SabreLite® 2000 Zone 1 Lamp Module

FL1 STANDARD	High
LIGHT OUTPUT 	
RUNTIME (hours/min) 	6h
BEAM DISTANCE (meters) 	177m
PEAK BEAM INTENSITY (candela) 	7852cd

Approvals

CE Ex - II 2G Ex e ib IIC T4 (Energizer), 150????C
 (Panasonic Plus, Duracell)
 Certificate: ITS09ATEX26181X