

LIGHTS
2000
SabreLite



Submersible 

SabreLite™ 2000 Flashlight

This powerful flashlight was designed with one thing in mind: SAFETY. It carries a variety of approvals, allowing safe use in many different hazardous environments and conditions. The SabreLite is o-ring sealed with a twist-on shroud and comes with a polarity battery guard tray that safeguards against dangerous "outgassing" of hydrogen from an accidentally reversed cell. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures. Unlike ordinary flashlights that produce a yellow beam, the SabreLite's incredibly bright Xenon lamp produces a powerful collimated white beam. Pelican's SabreLite is the leader in quality and performance.

Body Material: LEXAN EXL Resin

Minimum Pack 6 ea.

Packaged Weight: 6.8 oz.

Assorted Packs available - 2 black, 2 yellow, 2 orange.



Black



Orange








Yellow

SabreLite™ 2000 Flashlight Specifications SabreLite™ 2000 Flashlight Configurations

Cat. # Description

High	
LIGHT SOURCE	Xenon
BATTERIES	3 C Alkaline (Not included)
CHARGE TIME	N/A
VOLTAGE	4.5
LENGTH	7.79" (19.8 cm)
WEIGHT w/ BATTERIES	12.8 oz. (0.36 kg)
WEIGHT w/o BATTERIES	5.31 oz. (0.15 kg)

FL 1 STANDARD	High	
LIGHT OUTPUT 	53 LUMENS	
RUNTIME (hours/min) 	5h	
BEAM DISTANCE (meters) 	158m	
PEAK BEAM INTENSITY (candela) 	6234cd	
WATERPROOF & SUBMERSIBLE 	IPX7	IPX7

2000 SabreLite™ 2000 Flashlight (Carded)

2000PL SabreLite™ 2000 Flashlight w/ Photoluminescent Shroud (Carded)

NSN List

NSN #	Description
6230-01-295-1259	2000B Yellow
6230-01-496-3640	2000 Zone 1 (Peli)
6240-01-493-6640	2004 Lamp Module
6230-01-324-2951	2000B Orange
6230-01-281-3775	2000B Black

SabreLite™ 2000 Flashlight Accessories

Cat. #	Description
2004	SabreLite™ 2000 Lamp Module
2003PL	Photoluminescent Shroud
8052OR	Traffic Wand (Orange)
8052YW	Traffic Wand (Yellow)

SabreLite™ 2000 Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.



Class I, II, Div. 2; Gp. ABCD/G , T3C.



LISTED

Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class I; Zone 1; Gp.IIA; IIB; T3C



IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com