



Save as PDF



Peli lights - Zone 0 Lights - Alkaline Incandescent Worklights

Same features as L1 1930 LED with static-dissipation materials body. Being certified to ATEX safe for use in high-risk hazardous locations, Zone 0 (Category 1) areas, L1 1930Z0 LED is ideal for professionals who work in chemical, pharmaceutical, power, oil and gas, and fire rescue industries.



Gray

**Peli lights - Zone 0 Lights - Alkaline Incandescent Worklights
ANSI FL1 Specifications**

| | High | |
|-----------------------------|-----------------------------|--|
| LIGHT SOURCE. | LED | |
| BATTERIES | 4 LR 44 Alkaline (Included) | |
| CHARGE TIME | N/A | |
| VOLTAGE | 6 | |
| LENGTH | 6.7 cm (2.64") | |
| WEIGHT W/ BATTERIES | 0.17 kg (6 oz.) | |
| WEIGHT W/O BATTERIES | 0.02 kg (0.63 oz.) | |

LIGHT OUTPUT

RUNTIME (hours/min)

BEAM DISTANCE (meters)

PEAK BEAM INTENSITY (candela)

| FL 1 STANDARD | High | |
|---------------|--------|--|
| | | |
| | 4h 15m | |
| | 17m | |
| | 70cd | |

Materials

| Body | Lens | Shroud | Switch Type |
|---------------------|----------------------------|---------------------|-------------------|
| Polycarbonate Resin | Polycarbonate Resin | Xenoy Polymer Resin | On/Off end switch |
| Clip | Contact, Spring & Retainer | O-Ring | Night Vision Film |
| N/A | Phosphore/Bronze | Ethylene Propylene | N/A |

Configuration

| Cat. # | Description |
|--------|-------------|
|--------|-------------|

Peli lights - Zone 0 Lights - Alkaline Incandescent Worklights Accessories

No accessories are currently available for this product

Approvals

CE Ex - II 1 G Ex ia IIC T4/T6
Certificate: EPSILON 07ATEX 2280X