#### Uncontrolled document as of April 9, 2014. Refer to website for up to date specifications.

# Save as PDF | 📅 Print | Close Window







## CL2406-0303 Single Lid Case

- Molded-in, tongue-in-groove gasketed parting lines for splash resistance and tight seals, even after impact
- Reinforced corners and edges for additional impact protection
- Pelican's patented Comfort Grip Handles
- Recessed hardware for extra protection
- Positive anti-shear locks, which prevent lid separation after impact, and reduce stress on hardware
- Molded-in ribs and corrugations for secure, non-slip stacking, columnar strength, and added protection
- Patented molded-in metal inserts for catch and hinge attachment points, which provide strength and spread loads to the container walls
- One-piece construction, molded from lightweight, high-impact polyethylene

#### CL2406-0303 Single Lid Case Configurations



### CL2406-0303 Single Lid Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
26.87" x 8.62" x 7.81" (68.2 x 21.9 x 19.8 cm)	24.75" x 6.62" x 6.12" (62.8 x 16.8 x 15.5 cm)	
Lid Depth	Bottom Depth	Total Depth
3.06" (7.8 cm)	3.06" (7.8 cm)	6.12" (15.5 cm)
Weight	Buoyancy Max.	Lid Type
6.6 lbs. (2.99 kg)	58.76 lbs. (26.65 kg)	Removable Lid



#### Range Temperature

-20 / 140° F (-29 / 60° C)

All dimensions are approximate

 
 Pelican Products, Inc.

 23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com

