



2360 LED Flashlight

If you like the convenience of AA alkaline batteries, but need the performance of lithium batteries, the 2360 LED is the light for you. Using 2 standard AA alkaline batteries, the new 2360 LED emits a peak output of 163 lumens. With a run time of up to 3.5 hours, the last thing you will need to worry about while on the job, is a dim flashlight or dead batteries. Built-in battery level indicator ensures you will not be left in the dark.

Constructed with the most durable of materials: an aerospace grade aluminum body and an impact resistant LED lamp module, the 2360 LED keeps you on point without equipment failure. High and Low light output is available with a push of the tail button. It features a non-slip textured body for secure handling. The removable two way pocket clip securely attaches the 2360 to your pocket or the brim of your hat.

Body Material: Aluminum with Type II Anodized

Minimum Pack 6 ea.



Black

2360 LED Flashlight Specifications






2360 LED Flashlight Configurations

	High	Low
LIGHT SOURCE	LED	LED (Low)
BATTERIES	2 AA Alkaline (Included)	
CHARGE TIME	N/A	
VOLTAGE	3	
LENGTH	6.2" (15.7 cm)	
WEIGHT w/ BATTERIES	5.4 oz. (0.15 kg)	
WEIGHT w/o BATTERIES	3.7 oz. (0.1 kg)	

Cat. #	Description
2360	2360 LED Flashlight (Boxed)

2360 LED Flashlight Accessories

Cat. #	Description
2367	Cordura® Holster
1916	Break-away Safety Lanyard

	FL 1 STANDARD	High	Low		Strobe
LIGHT OUTPUT		250 LUMENS	24 LUMENS		250 LUMENS
RUNTIME (hours/min)		2h 15m	19h		
BEAM DISTANCE (meters)		151m	45m		151m
PEAK BEAM INTENSITY (candela)		5692cd	512cd		5692cd
WATER RESISTANT		IPX7	IPX7	IPX7	IPX7

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
 e-mail: CSR.Consumer@pelican.com • www.pelican.com