

LIGHTS
2000PL
SabreLite
Photoluminescent



SabreLite™ 2000 Photoluminescent Flashlight

Same features as the [SabreLite™ 2000 Flashlight](#) but outfitted with a lens ring that emits a bright glow in the dark. The new generation photoluminescent material in the plastic absorbs the energy from any light source - fluorescent lights, the sun, or even the flashlight's own beam. No more fumbling in the dark for your flashlight. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures.

Body Material: LEXAN EXL Resin

Minimum Pack 6 ea.

Packaged Weight: 6.8 oz.



Yellow

SabreLite™ 2000 Photoluminescent Flashlight Specifications

SabreLite™ 2000 Photoluminescent Flashlight Configurations






Cat. #	Description
--------	-------------

2000PL SabreLite™ 2000 Photoluminescent Flashlight (Carded)

SabreLite™ 2000 Photoluminescent Flashlight Accessories

Cat. #	Description
2004	SabreLite™ 2000 Lamp Module
8052OR	Traffic Wand (Orange)
8052YW	Traffic Wand (Yellow)

High	
LIGHT SOURCE	Xenon
BATTERIES	3 C Alkaline (Not included)
CHARGE TIME	N/A
VOLTAGE	4.5
LENGTH	7.79" (19.8 cm)
WEIGHT w/ BATTERIES	12.8 oz. (0.36 kg)
WEIGHT w/o BATTERIES	5.31 oz. (0.15 kg)

FL 1 STANDARD		High	
LIGHT OUTPUT		53 LUMENS	
RUNTIME (hours/min)		5h	
BEAM DISTANCE (meters)		158m	
PEAK BEAM INTENSITY (candela)		6234cd	
WATERPROOF & SUBMERSIBLE		IPX7	IPX7

SabreLite™ 2000 Photoluminescent Flashlight Approvals



Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.



Class I, II, Div. 2; Gp. ABCD/G , T3C.



Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class I; Zone 1; Gp.IIA; IIB; T3C



IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
 e-mail: CSR.Consumer@pelican.com • www.pelican.com