



L1™ 1930NVG LED Flashlight

The L1 1930NVG flashlight has the same features of the [L1 1930 LED](#) but equipped with a special lens that alters the color spectrum and cut the candlepower to preserve night vision. It's powered by 4 LR 44 1.5V alkaline coin cells (included) and compatible with NVG equipment.
Body Material: Polycarbonate Resin
Minimum Pack 12 ea.



Black

L1™ 1930NVG LED Flashlight Specifications L1™ 1930NVG LED Flashlight Configurations

Cat. #	Description
--------	-------------

High		
LIGHT SOURCE	LED	
BATTERIES	4 LR 44 Alkaline (Included)	
CHARGE TIME	N/A	
VOLTAGE	6	
LENGTH	2.64" (6.7 cm)	
WEIGHT w/ BATTERIES	0.9 oz. (0.03 kg)	
WEIGHT w/o BATTERIES	0.63 oz. (0.02 kg)	

	FL 1 STANDARD	High	
LIGHT OUTPUT			
RUNTIME (hours/min)			
BEAM DISTANCE (meters)			
PEAK BEAM INTENSITY (candela)			
WATER RESISTANT		IPX4	IPX4

1930NVG	L1™ 1930NVG LED Flashlight (Carded)
---------	-------------------------------------

L1™ 1930NVG LED Flashlight Accessories

Cat. #	Description
1939	Four 1.5V Alkaline Coin Cell Batteries
1946B	L1 1930NVG LED Attachment Kit

L1™ 1930NVG LED Flashlight Approvals



Listed 4S67/E184884 Class I, Div. 1 Gps.A,B,C,D, .



Ex ia IIC T4 IP65 IEC Ex TSA 06.0021X

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com