Uncontrolled document as of April 8, 2014. Refer to website for up to date specifications.







2720 LED Headlight

- Gesture Activation Control
- Variable Light Output
- Dual Red LED Night Vision

Gloved hands, wet hands or oily hands are not an issue when using the 2720 with Gesture Activation Control technology. Turn on the light with a wave of a hand. Additional features include: Low level red light that preserves night vision, for nighttime applications. Signaling red (S.O.S) beacon light. Optical 4x magnification allows for a wide or penetrating beam,. Including a variable light output from 100%-10%. Rubber head strap included.

Body Material: ABS

Minimum Pack 1 ea.



2720 LED Headlight Specifications

2720 LED Headlight Configurations

Cat. # Description

	High	Low
LIGHT SOURCE	LED	LED (Low)
BATTERIES	3 AAA Alkaline (Included)	
CHARGETIME		
VOLTAGE	4.5	
LENGTH	2.48" (6.3 cm)	
WEIGHT W BATTERIES	3.8 oz. (0.11 kg)	
WEIGHT WO BATTERIES	2.6 oz. (0.07 kg)	

ì	FL1 STANDARD	High	Low
LIGHT OUTPUT	シド	80 LUMENS	5 LUMENS
RUNTIME (hoursimin)	0	8h	175h
BEAM DISTANCE (meters)	I	56m	15m
EAK BEAM INTENSITY (candela)		790cd	60cd
WATER RESISTANT		IPX4	IPX4

2720

2720 LED Headlight (Carded)

Pelican Products, Inc.
23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail:CSR.Consumer@pelican.com • www.pelican.com