



Save as PDF



## VB3 2220 Zone 1 LED



Same features as VB3™ 2220 and being certified to ATEX safe for use in hazardous Zone 1 (Category 2) locations. The VB3 2220Z0 LED is ideal for professionals who work in areas with high risk of explosion such as chemical, pharmaceutical, power, oil and gas, and fire rescue.



Black Yellow

### VB3 2220 Zone 1 LED ANSI FL1 Specifications

<b>LIGHT SOURCE.</b>	High LED	
<b>BATTERIES</b>	2 CR2032 Lithium (Included)	
<b>CHARGE TIME</b>	N/A	
<b>VOLTAGE</b>	3	
<b>LENGTH</b>	8.9 cm (3.5")	
<b>WEIGHT W/ BATTERIES</b>	0.09 kg (3 oz.)	
<b>WEIGHT W/O BATTERIES</b>	0.02 kg (0.88 oz.)	

**LIGHT OUTPUT**

**RUNTIME (hours/min)**

**BEAM DISTANCE (meters)**

**PEAK BEAM INTENSITY (candela)**

<b>FL1 STANDARD</b>	High	
	34h	
	12m	
	38cd	

### Materials

Body	Lens	Shroud	Switch Type
Xylex Polymer Resin	N/A	N/A	Head flips up to activate
Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
Spring Loaded	Stainless Steel	Polymer	N/A

### Configuration

Cat. #	Description
--------	-------------

### VB3 2220 Zone 1 LED Accessories

No accessories are currently available for this product

### Approvals

CE - II 2 G Ex ib IIC T6  
Certificate: ITS09ATEX26182