



Save as PDF



MityLite™ 1965 LED Zone 0 Flashlight



YOUR WORLDWIDE PASSPORT THROUGH HAZARDOUS LOCATIONS

While working in hazardous locations, remember a light can be an ignition source. When you need the latest and brightest LED technology in a compact form factor, choose the new **MityLite™ 1965 LED** from Peli. Small enough to fit in your shirt pocket, yet bright enough to illuminate your work area.

Long lasting, energy efficient, bright LEDs, along with a compact package make the new **MityLite™ 1965 LED** the safety approved light for the job.



MityLite™ 1965 LED Zone 0 Flashlight

ANSI FL1 Specifications

	High	
LIGHT SOURCE.	LED	
BATTERIES	2 AAA Alkaline (Included)	
CHARGE TIME		
VOLTAGE	3	
LENGTH	13.9 cm (5.48")	
WEIGHT W/ BATTERIES	0.09 kg (3 oz.)	
WEIGHT W/O BATTERIES	0.03 kg (1.1 oz.)	

LIGHT OUTPUT
RUNTIME (hours/min)
BEAM DISTANCE (meters)
PEAK BEAM INTENSITY (candela)

FL 1 STANDARD	High	
	4h	
	51m	
	756cd	

Materials

Body	Lens	Shroud	Switch Type
EXL	Clear Polycarbonate	EXL	Rotary Switch Operation
Clip	Contact, Spring & Retainer	O-Ring	Night Vision Film
N/A	Phosphore Bronze	EPDM	NA

Configuration

Cat. #	Description
1965Z0	MityLite™ 1965 LED Zone 0 Flashlight

MityLite™ 1965 LED Zone 0 Flashlight Accessories

No accessories are currently available for this product

Approvals

CE - II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90??C Da

Certificate: TRAC10ATEX11241X

IECEx - IECEx TRC10.0005X - II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90

- Class I II III Div. 1 Grps. ABCDEFG T4

- Class I II III Div. 1 Grps. ABCDEFG T4