

LIGHTS
2010
SabreLite LED



Submersible 

SabreLite™ 2010 LED Flashlight

The SabreLite 2010 LED is Pelican's flagship LED flashlight. LED technology produces a white collimated beam that's as bright as an incandescent flashlight and provides 10,000 hours of lamp life and extended battery burn time. The rugged, light weight ABS resin body is submersible and a twist on/off lens shroud eliminates accidental discharge. It is powered by 3 C alkaline cells. The SabreLite 2010 Flashlight is the future of LEDs.

Body Material: EXL

Minimum Pack 1 ea.

Packaged Weight: 7.0 oz.



Black



Yellow






SabreLite™ 2010 LED Flashlight Specifications

SabreLite™ 2010 LED Flashlight Configurations

Cat. #	Description
--------	-------------

2010	SabreLite™ 2010 LED Flashlight (Carded)
------	---

High	
LIGHT SOURCE	LED
BATTERIES	3 C Alkaline (Not included)
CHARGE TIME	N/A
VOLTAGE	4.5
LENGTH	8.11" (20.6 cm)
WEIGHT w/ BATTERIES	13.4 oz. (0.38 kg)
WEIGHT w/o BATTERIES	5.36 oz. (0.15 kg)

FL 1 STANDARD	High	
LIGHT OUTPUT 	109 LUMENS	
RUNTIME (hours/min) 	32h	
BEAM DISTANCE (meters) 	144m	
PEAK BEAM INTENSITY (candela) 	5189cd	
WATERPROOF & SUBMERSIBLE 	IPX7	IPX7

2010 SabreLite™ 2010 LED Flashlight (Carved)

2010PL SabreLite™ 2010 LED Flashlight w/ Photoluminescent Shroud

NSN List

NSN #	Description
6230-01-530-0810	2010B Black
6230-01-620-2866	2010YW

SabreLite™ 2010 LED Flashlight Accessories

Cat. #	Description
2013PL	Photoluminescent Shroud
8052OR	Traffic Wand (Orange)
8052YW	Traffic Wand (Yellow)

SabreLite™ 2010 LED Flashlight Approvals

IECEx ITS11.0023 Ex ia IIC T4 Ga (Energizer E93), 145??C (Duracell MN1)

ETL US Class I II III Div. 1 Groups ABCDFG Operating Temp. T4 (Energizer E93), 145??C (Duracell MN1400), T3 (Panasonic LR14)
Intertek 3091325

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: CSR.Consumer@pelican.com • www.pelican.com